




NUP BEARING LTD



skf SAFS 22516-11 x 2.3/4 TLC SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAFS 22516-11 x 2.3/4 TLC

SAFS 22516-11 x 2.3/4 TLC Bearing 2D drawings and 3D CAD models

d_a	69.85 mm
D_a	140 mm
C_a	42.799 mm
A_1	88.9 mm
A_2	133.35 mm
S	4.763 mm
b_a	34.131 mm
H	174.625 mm
H_1	88.9 mm
H_2	31.75 mm
J min.	244.475 mm
J max.	279.4 mm
J_1	53.975 mm
L	330.2 mm
N_1	19.05 mm
R_1	53.181 mm
R_2	21.431 mm
R_G	3/8 NPT
P_G	1/8 NPT
h	31.75 mm
Housing	FSAFS 516
Bearing	22216 EK
Adapter sleeve assembly	SNW 16x2.3/4
Stabilizing ring	SR-16-13
Labyrinth ring	2 x LOR 45



NUP BEARING LTD

PosiTrac Plus contact element	2 x B10724-44
End plug (suffix Y)	EPR 8
Max. speed for PosiTrac Plus seal	2150 r/min
P _{60°}	138 kN
P _{90°}	82.7 kN
P _{120°}	49.8 kN
P _{150°}	44.5 kN
P _{180°}	52.5 kN
P _a	7.83 kN
Mass pillow block	21.3 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N · m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.625 in
Initial grease fill	87.885 g